

Huebsch is the answer.



**50, 55 and 75 lb LoadStar™
OPL Tumblers**



 **Huebsch®**



Huebsch is the answer.

Anybody can sell you laundry equipment and discuss the merits of each nut and bolt. However, at Huebsch, our priority is answering your questions about how working with us will make your business easier to run and more profitable.

Customers have selected Huebsch products for their ease of use, supreme durability and because owning a Huebsch product brings a service and support network that's unmatched within the industry. For profitability, reliability and ease of use, Huebsch is the answer.

Big Performance

Why are 50 and 75 lb Huebsch LoadStar™ commercial dryers a good fit for my laundry?

Extra capacity.

Huebsch LoadStar™ 50 and 75 lb dryers offer the sizable capacity to effectively meet the needs of most medium and large scale laundries.

Highly efficient.

Huebsch large capacity drying tumblers give you not only extra capacity, but also superior efficiency with a high performance heater box. Sealed cylinder rims and a concentrated airflow pattern help to keep utility costs down and the laundry yielding maximum throughput volumes.

Additional Features

Beyond efficiency, what LoadStar™ features help improve my operation overall?

Large door openings.

Huebsch is the answer for fast loading and unloading with 26 7/8" door openings. When you're able to load and unload quickly, your laundry is able to keep loads moving.

Easy to clean.

A self-cleaning lint screen means fast, efficient lint removal from the dryer's large storage area.



Tangle tamer.

A reversing option (offered on 3 phase models) is particularly useful for laundries washing sheets or large table linens. The reversing cylinder helps eliminate tangling of such items, saving employees valuable time.

A Great Finish

How will these dryers help my laundry deliver fantastic finished results?

Staying in control.

LoadStar™ models can be equipped with either Huebsch's extremely user-friendly Micro-Display control or Dual Digital control. The Micro-Display control features four preset drying cycles and offers the ability to further customize programs. This programmability enables you to get the results you desire every load with no wasteful overdrying. With the dual digital timer control, operators can set drying time (0-60 minutes), cool down time (0-15 minutes) and temperature (high, medium, low, no heat). Additional user-friendly features include a one-touch cycle repeat, automatic anti-wrinkle extended tumble and time remaining display.



Micro-processor Control



Dual Digital Control

Better Results, Small Package

How can my laundry add drying capacity without taking up more precious floor space?

New 55 lb LoadStar™ features increased capacity.

While Huebsch's newest dryer offers five more pounds of capacity than a 50 lb tumbler, it's 4" narrower, enabling it to fit easily through a standard 36" door opening. It's also more than a foot shorter.

A perfect blend of speed and efficiency.

Laundries benefit from the 55lb drying tumbler's axial airflow process, which helps it out-perform many competing 50 lb radial airflow dryers in both speed and efficiency.



50, 55 and 75 lb Tumbler Specifications

Models	H50	H55	H75
Control Options	Programmable (OM), Electronic (QT)	Programmable (OM), Electronic (QT)	Programmable (OM), Electronic (QT)
Dry Weight Capacity - lb (kg)	50 (22.7)	55 (24.9)	75 (34)
Width - in (mm)	38 5/8" (981)	34 1/2" (876)	38 5/8" (981)
Depth - in (mm)	47" (1194)	53 5/8" (1362)	53" (1346)
Height - in (mm)	76 5/8" (1946)	66 3/4" (1695)	76 5/8" (1946)
Cylinder Depth - in (mm)	30" (762)	35" (889)	36" (914)
Cylinder Diameter - in (mm)	37" (939)	33" (838)	37" (939)
Cylinder Volume - cu. ft. (liters)	18.6 (528)	17.3 (491)	22.4 (634)
Door Opening Size - in (mm)	26 7/8" (683)	26 7/8" (683)	26 7/8" (683)
Airflow - cfm (liters/sec.)	750 (354)	50 Hz: 600 (283)	50 Hz: 750 (354)
Energy Data	Gas Models: 50 Hz: 130,000 Btu/hr (38.1 kW) Steam Models: At 100 psi (6.9 bar): 5.1 BHP Electric Models: 30 kW	Gas Models: 50 Hz: 102,000 Btu/hr (29.9 kW) Steam Models: N/A Electric Models: 27 kW	Gas Models: 50 Hz: 165,000 Btu/hr (65.9 kW) Steam Models: At 100 psi (6.9 bar): 6.1 BHP Electric Models: 30 kW
Electrical Specifications	Non-Rev 100/200/50/1 N/A 230-240/50/1 6.3 200/50/3 3.3 230-240/50/3 3.1 380/50/3 N/A 400-415/50/3 N/A 380/400-415/50/3 1.6/1.6	Non-Rev 10.0/6.2 5.5 N/A N/A 2.0 2.0 N/A	Non-Rev N/A 6.7 3.5 3.5 N/A N/A 1.8/1.8
Plumbing Connection - in (mm)	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: N/A	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT
Shipping Dimensions	Width 41 1/2" (1054) Depth 52 1/8" (1323) Height 81" (2057)	Width 35 1/2" (902) Depth 59" (1499) Height 72" (1829)	Width 41 1/2" (1054) Depth 56 3/8" (1433) Height 81" (2057)
Net Weight - lb (kg)	545 (247)	435 (197)	615 (279)
Shipping Weight - lb (kg)	602 (273)	476 (216)	677 (307)
Agency Approvals	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame	cCSA _{US} , CE, CSA Star, CSA Flame

Tumbler models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumbler.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2009 Alliance Laundry Systems LLC

