



## Horizon Range

**Ultra High Efficiency  
washers, dryers,  
stack dryers and  
laundry centres**



- Vended (coin/card) and OPL (free vend) models
- Washer - SF3JX (coin) - SF3JM (OPL)
- Dryer - NDEBX/NDGBX (coin) - NDEM/NDGM (OPL)
- Stack dryer - SSEBX/SSGBX (coin) - SSEBM/SSGBM (OPL)
- Laundry centre - ST1JX/ST2JX (coin) - ST1JM/ST2JM (OPL)

## Horizon Range

SPECIFICATIONS	SINGLE WASHER	SINGLE DRYER	STACK DRYER	LAUNDRY CENTRE - WASHER AND DRYER
Models	SF3JX (coin) SF3JM (OPL)	NDEBX (coin) NDGBX (coin) NDEM (OPL) NDGM (OPL)	SSEBX/SSGBX (coin) SSEBM/SSGBM (OPL)	ST1JX/ST2JX (coin) ST1JM/ST2JM (OPL)
Capacity (kg)	9.5	8.2	8.2/8.2	9.5/8.2
Drum Volume (litres)	96.8	198	198/198	96.8/198
Width (mm)	683	683	683	683
Depth (mm)	756	711	711	756
Height (mm)	1126	1126	1986	1986
Spin Speed - G Force (RPM)	440 (1200)	-	-	440 (1200)
Colour	White	White	White	White
Motor Size (HP)	0.9	1/3	2 x 1/3	0.9-1/3
Heat Source	Electric	Electric/Gas	Electric/Gas	Electric/Gas
Gas Connection	-	9.5 mm	2 x 9.5mm	9.5 mm
Gas Consumption (BTU/Hr)	-	22,500	22,500 each	22,500
Exhaust Outlet Size (mm)	-	102	2 x 102	102
Exhaust Airflow (litres/sec)	-	105	105 ea	105
Water Pressure (Bar)	1.4 - 8.3	-	-	1.4 - 8.3
Electrical Requirements	Electric requirements - 240/50/1 Single Washer 5.2kw (2 x 2.4kw elements) install on 3phase 16a or single phase 32a breaker or 2.8kw (1 x 2.4kw element) install on a 16a breaker or 13a plug top for boiler fed no electric heat	Electric requirements - 240/50/1 Single Dryer Electric 5.2kw (1 x 4.8kw element) install on single phase 32a breaker or 13a plus top Gas models only	Electric requirements - 240/50/1 Electric dryers - 2 x 5.2kw (2 x 2.4kw element) install on 2 x 1ph 16a breakers Gas dryers - 2 x 13a plug tops only	
Net Weight (kg)	122	70	125	177
Shipping Weight (kg)	132	75	132	193
Shipping Width (mm)	737W/832D/1156H	737W/832D/1156H	737W/832D/2032H	737W/832D/2032H
Approvals	CE, WRAS	CE	CE	CE, WRAS

\* A variety of electrical configurations are available - ask your distributor for details.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

11.18/150

**Armstrong**  
COMMERCIAL LAUNDRY SYSTEMS

**Head Office:** Unit 11, Arnhem Road, Bone Lane,  
Newbury, Berkshire RG14 5RU

**Sales:** +44 (0)1635 263410

**Parts:** +44 (0)1635 263415

**Service:** +44 (0)1635 263425

**Switchboard:** +44 (0)1635 263400

**Email:** enquiries@armstronglaundry.com

**Web:** www.armstronglaundry.com

**Scottish office**

46 Kelvin Avenue,  
Hillington Park, Glasgow G52 4LT

**Tel:** +44 (0)141 892 2390

**Email:** scotland@armstronglaundry.com

